S60 IP Indoor Station

Smart Intercom

10.1-inch Android IP Indoor Station featuring a smart touchscreen, video intercom, mobile app connectivity, remote door unlocking and 8-channel wired alarm integration. Supports live video monitoring from door stations and linked IP cameras.



Overview

The S60 IP Indoor Station is an advanced smart video intercom and home security solution featuring a stylish design and a 10.1-inch capacitive touchscreen with 1280 × 800 HD resolution. Powered by Android 7.1, it provides convenient access control, visitor communication and integrated security monitoring.

Key features

- 10.1-inch capacitive touchscreen with 1280 × 800 resolution.
- Android 7.1 operating system with 4GB Flash and 1GB RAM.
- Video intercom and remote door unlocking through the mobile app.
- Supports 8-channel wired alarm zones for home security integration.
- Live video monitoring from door stations and linked IP cameras.
- H.264 video encoding with VGA / 720P video support.
- Built-in loudspeaker and microphone for two-way audio communication.
- Supports up to 100 contacts, 100 intercom logs and 100 alarm logs.
- Stores up to 50 messages.
- Network connectivity through RJ45 Ethernet and Wi-Fi.
- RS485 interface for system integration.
- Wall-mounted installation with a slim 16.8 mm profile.
- Available in Black and White finishes

Applications

- Parameter: Specification
- Display: 10.1-inch LCD
- Resolution: 1280 × 800
- Operating System: Android 7.1
- Flash / RAM: 4GB / 1GB
- Audio Encoding: G.711

- Network: TCP/IP, Wi-Fi
- Power Supply: 12–24V DC
- Power Consumption: 4W Standby / 11W Maximum
- Protection Rating: IP30
- Dimensions: 260 × 185 × 16.8 mm
- Operating Temperature: -10°C to +50°C
- Installation: Wall Mounted

Specifications

Parameter	Specification
Display	10.1-inch LCD
Resolution	1280 × 800
Operating System	Android 7.1
Flash / RAM	4GB / 1GB
Audio Encoding	G.711
Network	TCP/IP, Wi-Fi
Power Supply	12–24V DC
Power Consumption	4W Standby / 11W Maximum
Protection Rating	IP30
Dimensions	260 × 185 × 16.8 mm
Operating Temperature	-10°C to +50°C
Installation	Wall Mounted

Contact: contact@radiantsmartx.com | www.radiantsmartx.com

© 2019–2026 Radiant Solaris Ltd. All rights reserved. The Radiant™ logo is a registered trademark of Radiant Solaris Ltd. All specifications are subject to change without notice.