S70 IP Outdoor Station

Smart Intercom · Model S70

IP Outdoor Station with PoE Power Supply, IP65 Waterproof & Dustproof Protection, 2MP HD Wide-Angle Camera, Multiple Door Unlocking Options (Card, Indoor Station & Mobile App), and Advanced Security Alerts for Forced Entry, Door Left Open, Motion Detection and Resident Alerts.



Overview

The IP Video Door Station is an advanced access control and home security device powered by an embedded Linux operating system. It features a 2MP HD camera with a 129° horizontal wide-angle view, H.264 video encoding and white-light illumination for clear image capture. The device supports multiple door unlocking methods, including RFID card, indoor monitor and remote access through a mobile application.

Equipped with a built-in loudspeaker and microphone, it enables two-way audio communication with visitors. Its advanced security features include forced-door opening alerts, door timeout alarms, motion detection and resident security notifications.

The unit supports standard TCP/IP networking, PoE connectivity, RS485 interfaces and 12V power output. Its IP65 waterproof and dustproof rating and IK07 impact protection make it suitable for reliable indoor and outdoor installation. It offers both flush-mounted and wall-mounted installation options.

Key features

- 2MP HD camera with 129° wide-angle viewing.
- H.264 video compression with VGA / 720P resolution.
- White-light illumination for enhanced visibility.
- Two-way audio communication with built-in speaker and microphone.
- Multiple door unlocking options: RFID card, indoor station and mobile app.
- Supports up to 20,000 access cards.
- Advanced security alerts for forced entry, door timeout and motion detection.
- TCP/IP network connectivity with PoE support.
- RS485 interface and 12V power output.
- IP65 waterproof and dustproof protection.
- IK07 impact resistance.
- Flush-mounted and wall-mounted installation options.

Applications

- Home

Specifications

Protocols	TCP/IP, UDP, HTTP, DNS, RTP
Connectivity / radio	PoE
Power supply	12V
Operating humidity	-30°C ~ +60°C
Dimensions	85*162*30mm
Installation / mounting	Flush install / Wallmounted

Contact: contact@radiantsmartx.com | www.radiantsmartx.com

© 2019–2026 Radiant Solaris Ltd. All rights reserved. The Radiant™ logo is a registered trademark of Radiant Solaris Ltd. All specifications are subject to change without notice.